



Series

Page

M23 Series

1-8

IP rating: IP67
Coupling: threaded
Shield: shielded / unshielded
No. of contact: for power: 6,8
for signal: 9,12,17,19



SF Series

9-17

IP rating: IP67
Coupling: push-pull
No. of contact: SF6: 2-5
SF8: 2-8
SF10: 2-5
SF12: 2-9
SF16: 2-10
SF20: 2-12



SA Series

19-26

IP rating: IP67
Coupling: push-pull
No. of contact: SA6: 2-5
SA8: 2-8
SA10: 2-5
SA12: 2-9
SA16: 2-10
SA20: 2-12
SA28: 2-26



ST Series

29-30

IP rating: IP67
Coupling: threaded
No. of contact: 2-9



Series

Page

SP Series

31-36

IP rating: IP68
Coupling: threaded
No. of contact: SP11: 2-5
SP13: 2-9
SP17: 2-10
SP21: 2-12
SP29: 2-26



SY Series

37-40

IP rating: IP67
Coupling: bayonet
No. of contact: SY13: 2-9
SY17: 2-10
SY21: 2-12



WA22 Series

43-45

IP rating: IP67
Coupling: threaded
No. of contact: 3+PE, 6+PE



WAC3 Series

47

IP rating: IP65
Coupling: bayonet
No. of contact: 3



Series	Page
--------	------

RJ45F Series

48

IP rating: IP67
Coupling: bayonet



WP Series

49-50

IP rating: IP44 , IP55
Coupling: bayonet
No. of contact: 2-12



WL52 Series

51-55

IP rating: IP67
Coupling: threaded
No. of contact: 19



WD Series

59-60

IP rating: IP55, IP65
Coupling: threaded
No. of contact: 4, 15



Series

Page

WS Series

61-68

IP rating: for indoor only
Coupling: threaded
No. of contact: 2-61



WF Series

69-76

IP rating: IP44, IP55, IP65, IP67
Coupling: threaded
No. of contact: 2-61



WY Series

77-83

IP rating: IP44, IP55, IP65, IP66, IP67
Coupling: bayonet
No. of contact: 2-61



Cable gland

85

PG7, PG9, PG11, PG13.5, PG16, PG21,
PG29, PG36



Series

Page

Solder contact spec

87-88

For WP, WS, WF, WY series



Crimp contact spec and tool

89-92

For SF, SA, SP, SY, WP, WS, WF, WY series

